





Technical Data

**FRAMELESS
STAINLESS STEEL
MIRROR**

**B-1556
SERIES**



Recommended Mounting Height Off Floor
for Barrier-Free Design
40" Max. 1015mm

STANDARD B-1556 SERIES MIRRORS

Model No.	Overall Size		Number of Mounting Screws
	(W)	(H)	
B-1556 1620	15-1/2" (394mm)	19-1/2" (495mm)	4
B-1556 1824	17-1/2" (445mm)	23-1/2" (597mm)	4
B-1556 1830	17-1/2" (445mm)	29-1/2" (749mm)	4
B-1556 2436	23-1/2" (597mm)	35-1/2" (902mm)	4

MATERIALS:

Mirror — 22-gauge (0.8mm), type-430 stainless steel with bright polished finish. Mirror has 1/4" (6mm) return.

Backing — 1/4" (6mm) thick tempered masonite.

INSTALLATION:

Mount mirror on wall with screws, furnished by manufacturer, at points indicated by an S. For plaster or dry wall construction, provide concealed backing to comply with local building codes, then secure unit with sheet-metal screws furnished. For other wall surfaces, provide fiber plugs or expansion shields for use with sheet-metal screws furnished, or provide 1/8" (3mm) toggle bolts or expansion bolts.

SPECIFICATION:

Frameless stainless steel mirror shall be type-430 stainless steel with bright polished finish. Mirror shall have 1/4" (6mm) return concealing 1/4" (6mm) tempered masonite backing. Mirror shall be furnished with mounting screws and finishing washers. Manufacturer's service and parts manual shall be provided to the building owner/manager upon completion of project.

Mirror shall be Model B-1556 _____ (insert width and height) of Bobrick Washroom Equipment, Inc., Clifton Park, New York; Jackson, Tennessee; Los Angeles, California; Bobrick Washroom Equipment Company, Scarborough, Ontario; Bobrick Washroom Equipment Pty. Ltd., Australia; and Bobrick Washroom Equipment Limited, United Kingdom.